



MABEL CERA

water-based anti-slip wax

Line

PROTECTIVE

Function

SLIP-PROOF PROTECTIVE AND POLISHING.SUITABLE FOR ALL POLISHED SURFACES TO BE PROTECTED WITH A FILM OF WAX WITH STRONG SLIP-PROOF CHARACTERISTICS

Materials

SPECIALLY FORMULATED FOR MARBLES, GRANITES, POLISHED NATURAL STONE. CAN ALSO BE APPLIED TO WOOD AND PLASTIC.

How to use

APPLICATION:□

1.□Spread a film of wax on the surface to be treated using the sprayer provided or a cotton cloth, with rotary movements and passing over the same areas several times.□

2.□Make sure the wax is applied uniformly over the entire surface.□

Wait a few minutes (2-5) to allow the wax to properly absorb and attach to the floor. Wait another 5-10 minutes to allow it to dry well and then proceed to polish.□

POLISHING:□

Rub and polish with a clean cloth until eventual marks or streaks disappear. □

NOTE:□

For a stronger antislip effect apply one or two coats more according to the absorption capacity of the surface and the required effect□

Packaging

L.1-5

Characteristics

WATER-BASED WAX AND RESIN EMULSION.

Important

A PRELIMINARY TEST IN A SMALL, HIDDEN, AREA IS RECOMMENDED BEFORE THE APPLICATION.□

USE ONLY ORIGINAL CONTAINERS;NEVER POUR THE PRODUCT INTO OTHER METAL OR GLASS CONTAINERS.□