



## VELOX PL 95

protective treatment for walls,antigraffiti

### Line

PROTECTION

### Function

Prevents absorption on the walls of graffiti such as spray paint, marker ink, etc. Prevents the adhesion of poster glue. Protection for absorbent, unfinished, and plastered walls. Removal of graffiti from treated surface is fast and easy with OK Come Prima.

### Materials

MARBLE, GRANITE, NATURAL and ARTIFICIAL ABSORBING STONES, SANDSTONES, CONCRETE, MASONRY, TRAVERTINE, VOLCANIC STONES etc.

### How to use

Combine the content of the two tins and mix. Product is usable for some hours. Apply to clean and dry surface with brush, cloth or by spraying. Catalysis takes 48 to 60 hours and reticulation is complete in about 7 days. Avoid driving rain in the first 24 hours,.

### Packaging

L.1-5

### Characteristics

Mixture of solvents, organic resins, reticulants and water-repellent substances

### Important

Mixture of solvents, organic resins, reticulants and water-repellent substances. Mixture of solvents, organic resins, reticulants and water-repellent substances. A PRELIMINARY TEST IN A SMALL, HIDDEN, AREA IS RECOMMENDED BEFORE THE APPLICATION. □  
USE ONLY ORIGINAL CONTAINERS; NEVER POUR THE PRODUCT INTO OTHER METAL OR GLASS CONTAINERS □